

RobotLog2RQM

v. 1.2.1

Tran Duy Ngoan

14.06.2023

Contents

| | | |
|----------|---------------------------------------|----------|
| 1 | Introduction | 1 |
| 2 | Description | 2 |
| 2.1 | Get Robot Framework XML result | 2 |
| 2.2 | Tool features | 2 |
| 2.2.1 | Usage | 3 |
| 2.2.2 | Basic import feature | 3 |
| 2.2.3 | Verify the given arguments | 4 |
| 2.2.4 | Import multiple *.xml result files | 4 |
| 2.2.5 | Create missing Test Case on RQM | 4 |
| 2.2.6 | Update existing Test Case on RQM | 5 |
| 2.3 | Robot Testcase information onRQM: | 5 |
| 3 | CRQM.py | 7 |
| 3.1 | Function: get_xml_tree | 7 |
| 3.2 | Class: CRQMClient | 7 |
| 3.2.1 | Method: login | 8 |
| 3.2.2 | Method: verifyProjectName | 8 |
| 3.2.3 | Method: disconnect | 8 |
| 3.2.4 | Method: config | 8 |
| 3.2.5 | Method: userURL | 9 |
| 3.2.6 | Method: integrationURL | 9 |
| 3.2.7 | Method: webIDfromResponse | 10 |
| 3.2.8 | Method: webIDfromGeneratedID | 10 |
| 3.2.9 | Method: getResourceByID | 10 |
| 3.2.10 | Method: getAllByResource | 11 |
| 3.2.11 | Method: getAllBuildRecords | 11 |
| 3.2.12 | Method: getAllConfigurations | 11 |
| 3.2.13 | Method: getAllTeamAreas | 11 |
| 3.2.14 | Method: addTeamAreaNode | 12 |
| 3.2.15 | Method: createTestcaseTemplate | 12 |
| 3.2.16 | Method: createTCERTemplate | 13 |
| 3.2.17 | Method: createExecutionResultTemplate | 14 |
| 3.2.18 | Method: createBuildRecordTemplate | 15 |
| 3.2.19 | Method: createConfigurationTemplate | 15 |
| 3.2.20 | Method: createTSERTemplate | 16 |
| 3.2.21 | Method: createTestsuiteResultTemplate | 16 |

| | | |
|----------|--|-----------|
| 3.2.22 | Method: createResource | 17 |
| 3.2.23 | Method: createBuildRecord | 18 |
| 3.2.24 | Method: createConfiguration | 18 |
| 3.2.25 | Method: updateResourceByID | 19 |
| 3.2.26 | Method: linkListTestcase2Testplan | 19 |
| 3.2.27 | Method: linkListTestcase2Testsuite | 20 |
| 4 | robotlog2rqm.py | 21 |
| 4.1 | Function: get_from_tags | 21 |
| 4.2 | Function: convert_to_datetime | 21 |
| 4.3 | Function: process_suite_metadata | 22 |
| 4.4 | Function: process_metadata | 22 |
| 4.5 | Function: process_suite | 22 |
| 4.6 | Function: process_test | 23 |
| 4.7 | Function: RobotLog2RQM | 23 |
| 4.8 | Class: Logger | 23 |
| 4.8.1 | Method: config | 24 |
| 4.8.2 | Method: log | 24 |
| 4.8.3 | Method: log_warning | 24 |
| 4.8.4 | Method: log_error | 25 |
| 5 | Appendix | 26 |
| 6 | History | 27 |

Chapter 1

Introduction

RobotLog2RQM helps to import the Robot result file(s) as ***.xml** format into IBM® Rational® Quality Manager - RQM resources.

It provides ability (**CRQM Class**) to interact with RQM resources such as test plan, test case, build, ... via [RqmAPI](#) to:

- Get RQM resource: by given ID or all vailable entities of resource type.
- Update RQM resource: by given ID.
- Create new RQM resource: with resource templates under [RQM.templates](#) folder.

So that **RobotLog2RQM** tool can:

- Create all required resources (*Test Case Excution Record*, *Test Case Execution Result*, ...) for new testcase on RQM.
- Link all testcases to provided testplan.
- Add new test result for existing testcase on RQM.
- Update existing testcase on RQM.

Chapter 2

Description

2.1 Get Robot Framework XML result

In order to manage test cases and their results with RQM, some traceable information such as version, testcase ID, component, ... are required.

So that the **RobotLog2RQM** tool can know which importing test results are belong to (Test Case) or linked with (Build Record, Test Environment) on RQM.

These information should be provided in **Metadata** (for the whole testsuite/execution info: version, build, ...) and **[Tags]** information (for specific testcase info: component, testcase ID, requirement ID, ...) of Robot Framework testcase. Then when executing Robot testcase(s), the generated Robot result file (default is *output.xml*) will contain all of them and ready for importing.

Sample Robot Framework testcase with the necessary information for importing to RQM:

```
*** Settings ***
Metadata    project           ROBFW           # Test Environment on RQM for linking
Metadata    version_sw       SW_VERSION_0.1   # Build Record on RQM for linking
Metadata    machine          ${COMPUTERNAME}   # Hostname attribute in RQM Test Case Result
Metadata    component        Import_Tools     # Component attribute in RQM Test Case
Metadata    team-area        Internet Team RQM # team-area (case-sensitive) on RQM for linking

*** Test Cases ***
Testcase 01
    [Documentation]    This test is traceable with provided tcid
    [Tags]            TCID-1001    FID-112    FID-111    ↔
    ↪ robotfile-https://github.com/test-fullautomation
    Log                This is Testcase 01

Testcase 02
    [Documentation]    This new testcase will be created if -createmissing argument
    ...               ... is provided when importing
    [Tags]            FID-113    robotfile-https://github.com/test-fullautomation
    Log                This is Testcase 02
```

Listing 2.1: Sample Robot Framework testcase

Hint



In case you are using RobotFramework AIO with **RobotFramework.Testsuites** library for executing Robot testcase(s). You do not need to define above highlighted **Metadata** in your Robot test case.

These **Metadata** information will be defined implicitly within the **Suite Setup** bases on your environment and configuration in *.json file.

2.2 Tool features

After getting the Robot Framework *.xml result file(s), you can use the **RobotLog2RQM** tool to import them into RQM.

Its usage and features are described as following sections.

2.2.1 Usage

Use below command to get tools's usage:

```
RobotLog2DB -h
```

The tool's usage should be showed as below:

```
usage: RobotLog2RQM (RobotXMLResult to RQM importer) [-h] [-v] [--recursive]
          [--createmissing] [--updatetestcase] [--dryrun]
          resultxmlfile host project user password testplan
```

RobotLog2RQM imports XML result files (default: output.xml) generated by the Robot Framework into an IBM Rational Quality Manager.

positional arguments:

```
resultxmlfile    absolute or relative path to the xml result file
                  or directory of result files to be imported.
host             RQM host url.
project          project on RQM.
user            user for RQM login.
password        password for RQM login.
testplan        testplan ID for this execution.
```

optional arguments:

```
-h, --help        show this help message and exit
-v, --version     Version of the RobotLog2RQM importer.
--recursive       if set, then the path is searched recursively for
                  log files to be imported.
--createmissing   if set, then all testcases without tcid are created
                  when importing.
--updatetestcase  if set, then testcase information on RQM will be updated
                  bases on robot testfile.
--dryrun         if set, then verify all input arguments
                  (includes RQM authentication) and show what would be done.
```

As above instruction, **RobotLog2RQM** tool requires 5 positional arguments consists of:

- The Robot result file/folder `resultxmlfile`
- The RQM authentication `host` , `project` , `user` , `password`
- The RQM `testplan` ID which will contains all importing test results

2.2.2 Basic import feature

Use the below command for the simple import the *output.xml* file to RQM project **ROBFW-AIO** which is hosted at <https://sample-rqm-host.com>

```
RobotLog2RQM output.xml https://sample-rqm-host.com ROBFW-AIO test_user test_pw 720
```

When command is executed, the tool will process with following steps:

- Login the RQM server with the provided credential, then verify the existences of given `project` , `testplan` on RQM
- Create RQM **Build Record** and **Test Environment** (if already provided in Robot test case and not existing on RQM)
- Create new RQM **Test Case Execution Record - TCER** (if it is not existing) bases on test case ID (defined `TCID-xxx` in `[Tags]` of Robot Test Cases) and `testplan` ID
- Create new RQM **Test Case Execution Result** which contents the detail and result state of Robot test case
- Link all test case(s) to provided `testplan`

2.2.3 Verify the given arguments

In case you just want to verify whether the given **.xml* file/folder and the RQM authentication in arguments are corrected or not, the optional argument `--dryrun` will help to do it.

In the dryrun mode, **RobotLog2RQM** will not create any resources on RQM, it just verify:

- The given Robot result file/folder is valid or not
- The given RQM authentication is correct or not
- The given RQM project and testplan are existing or not

2.2.4 Import multiple *.xml result files

RobotLog2RQM accepts the first argument `resultxmlfile` can be a single file or the folder that contains multiple Robot result files.

When the folder is used, **RobotLog2RQM** will only search for **.xml* file under given directory and exclude any file within subdirectories as default.

In case you have result file(s) under the subdirectory of given folder and want these result files will also be imported, the optional argument `--recursive` should be used when executing **RobotLog2RQM** command.

When `--recursive` argument is set, **RobotLog2RQM** will walk through the given directory and its subdirectories to discover and collect all available **.xml* for importing.

For example: your result folder has a structure as below:

```
logFolder
|_____ result_1.xml
|_____ result_2.xml
|_____ subFolder_1
|           |_____ result_sub_1.xml
|           |_____ subSubFolder
|                   |_____ result_sub_sub_1.xml
|_____ subFolder_2
|           |_____ result_sub_2.xml
```

- Without `--recursive` : only **result_1.xml** and **result_2.xml** are found for importing.
- With `--recursive` : all **result_1.xml**, **result_2.xml**, **result_sub_1.xml**, **result_sub_2.xml** and **result_sub_sub_1.xml** will be imported.

2.2.5 Create missing Test Case on RQM

By default, **RobotLog2RQM** tool will not touch (create, update) any RQM Test Case.

If the `TCID-xxx` information is missing in `[Tags]` of Robot Test Case, the error message will be raised for that importing Test Case and process with the next Test Cases

```
ERROR: There is no 'tcid' information for importing test 'Testcase 01'.
```

So that, in order to import those missing `TCID-xxx` Test Cases, the optional arguments `--createmissing` should be provided in the **RobotLog2RQM** arguments.

When `--createmissing` is used, **RobotLog2RQM** will help to create RQM Test Cases bases on the defined information in Robot Test Cases first to get the new testcase ID and use it for linking to related RQM resources **TCER**, **Test Case Execution Result** as basic feature.

The new testcase IDs for new Test Cases are also printed in the execution log, so that you can copy them and update to `TCID-xxx` information of Robot Test Cases for the next Robot execution. Then they will be available in the generated **.xml* result file for importing.

Please refer [Robot Testcase information on RQM](#) section for the reflections of defined information in Robot Test Case on RQM.

2.2.6 Update existing Test Case on RQM

In case the Test Case is existing on RQM, but you want to update its attribute(s) such as **Component**, **Description**, ... the optional argument `--updatetestcase` should be used.

RobotLog2RQM will update RQM Test Case resource bases on the defined information in Robot Test Case before creating its result.

Please refer [Robot Testcase information on RQM](#) section for the reflections of defined information in Robot Test Case on RQM.

2.3 Robot Testcase information on RQM:

For more detail about the mapping between the defined information from Robot Test Case to Robot result (*output.xml*) file and their reflections on RQM WebApp, please refer be mapping table:

| RQM data | | Robot Framework | |
|-----------------------------------|----------------------------|--|---|
| Resource | Attribute/ Field | Testsuite/Testcase | Output.xml |
| Build Record | Title | <code>Metadata version_sw Build</code> | <code>//suite/metadata/item[@name="version_sw"]</code> |
| Test Environment | Title | <code>Metadata project Environment</code> | <code>//suite/metadata/item[@name="project"]</code> |
| Test Case | ID | <code>[Tags] tcid-xxx</code> | <code>//suite/test/tags/tag[@text="tcid-xxx"]</code> |
| | Name | tesname | <code>//suite/test/@name</code> |
| | Team Area | <code>Metadata team-area Team_Area</code> | <code>//suite/metadata/item[@name="team-area"]</code> |
| | Description | test doc - <code>[Documentation]</code> | <code>//suite/test/doc/@text</code> |
| | Owner | provided <code>user</code> in cli | |
| | Component/ Categories | <code>Metadata component Component</code> | <code>//suite/metadata/item[@name="component"]</code> |
| | Requirement ID | <code>[Tags] fid-yyy</code> | <code>//suite/test/tags/tag[@text="fid-yyy"]</code> |
| | Robot File | <code>[Tags] robotfile-zzz</code> | <code>//suite/test/tags/tag[@text="robotfile-zzz"]</code> |
| Test Case Execution Record (TCER) | Owner | provided <code>user</code> in cli | |
| | Team Area | <code>Metadata team-area Team_Area</code> | <code>//suite/metadata/item[@name="team-area"]</code> |
| | Test Plan | Interaction URL to provided <code>testplan</code> in cli | |
| | Test Case | Interaction URL to provided testcase ID: provided tcid in <code>[Tags]: tcid-xxx</code> or generated tcid when using <code>-createmissing</code> | <code>//suite/test/tags/tag[@text="tcid-xxx"]</code> |
| | Test Environment | <code>Metadata project Environment</code> | <code>//suite/metadata/item[@name="project"]</code> |
| Test Result | Owner | provided <code>user</code> in cli | |
| | Tested By | provided <code>user</code> in cli - userid must be used | |
| | Team Area | <code>Metadata team-area Team_Area</code> | <code>//suite/metadata/item[@name="team-area"]</code> |
| | Actual Result | Test case result (PASSED, FAILED, UNKNOWN) | <code>//suite/test/status/@status</code> |
| | Host Name | <code>Metadata machine ↔ ↔ %{COMPUTERNAME}</code> | <code>//suite/metadata/item[@name="machine"]</code> |
| | Test Plan | Interaction URL to provided <code>testplan</code> in cli | |
| | Test Case | Interaction URL to provided testcase ID: provided tcid in <code>[Tags]: tcid-xxx</code> or generated tcid when using <code>-createmissing</code> | <code>//suite/test/tags/tag[@text="tcid-xxx"]</code> |
| | Test Case Execution Record | Interaction URL to TCER ID | |
| | Build | <code>Metadata version_sw Build</code> | <code>//suite/metadata/item[@name="version_sw"]</code> |
| | Start Time | Test case start time | <code>//suite/test/status/@starttime</code> |
| | End Time | Test case end time | <code>//suite/test/status/@endtime</code> |
| | Total Run Time | Calculated from start and end time | |
| | Result Details | Test case message log | <code>//suite/test/status/@text</code> |

Table 2.1: RQM data & Robot Framework testcase/output.xml

Chapter 3

CRQM.py

3.1 Function: get_xml_tree

Parse xml object from file.

Arguments:

- `file_name`
/ *Condition*: required / *Type*: str /
Path to file or file-like object.
- `bdttd.validation`
/ *Condition*: optional / *Type*: bool /
If True, validate against a DTD referenced by the document.

Returns:

- `oTree`
/ *Type*: `lxml.etree._ElementTree` object /
The xml etree object.

3.2 Class: CRQMClient

Imported by:

```
from RobotLog2RQM.CRQM import CRQMClient
```

CRQMClient class uses RQM REST APIs to get, create and update resources (testplan, testcase, test result, ...) on RQM - Rational Quality Manager

Resoure type mapping:

- `buildrecord`: Build Record
- `configuration`: Test Environment
- `testplan`: Test Plan
- `testsuite`: Test Suite
- `suiteexecutionrecord`: Test Suite Execution Record (TSER)
- `testsuitelog`: Test Suite Log
- `testcase`: Test Case
- `executionworkitem`: Test Execution Record (TCER)
- `executionresult`: Execution Result

3.2.1 Method: login

Log in RQM by provided user & password.

Arguments:

(no arguments)

Returns:

- bSuccess
/ Type: bool /
Indicates if the computation of the method login was successful or not.

3.2.2 Method: verifyProjectName

Verify the project name by searching it in project-areas XML response.

Arguments:

(no arguments)

Returns:

- bSuccess
/ Type: bool /
Indicates if the computation of the method verifyProjectName was successful or not.

3.2.3 Method: disconnect

Disconnect from RQM.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.4 Method: config

Configure RQMClient with testplan ID, build, configuration, createmissing, ...

- Verify the existence of provided testplan ID.
- Verify the existences of provided build and configuration names before creating new ones.

Arguments:

- plan_id
/ Condition: required / Type: str /
Testplan ID of RQM project for importing result(s).
- buildname
/ Condition: optional / Type: str / Default: None /
The Build Record for linking result(s). Set it to None if not be used, the empty name " " will lead to error.
- config_name
/ Condition: optional / Type: str / Default: None /
The Test Environment for linking result(s). Set it to None if not be used, the empty name " " may lead to error.
- createmissing
/ Condition: optional / Type: bool / Default: False /
If True, the testcase without tcid information will be created on RQM.

- `update_testcase`
/ *Condition*: optional / *Type*: bool / *Default*: False /
If True, the information of testcase on RQM will be updated bases on robot testfile.
- `suite_id` (optional)
/ *Condition*: optional / *Type*: str / *Default*: None /
Testsuite ID of RQM project for importing result(s).

Returns:*(no returns)***3.2.5 Method: userURL**

Return interaction URL of provided userID

Arguments:

- `userID`
/ *Condition*: required / *Type*: str /
The user ID.

Returns:

- `userURL`
/ *Type*: str /
The interaction URL of provided userID.

3.2.6 Method: integrationURLReturn interaction URL of provided resource and ID. The provided ID can be `internalID` (contains only digits) or `externalID`.**Arguments:**

- `resourceType`
/ *Condition*: required / *Type*: str /
The RQM resource type (e.g: "testplan", "testcase", ...).
- `id`
/ *Condition*: optional / *Type*: str / *Default*: None /
The ID of given resource.
 - If given: the specified url to resource ID is returned.
 - If None: the url to resource type (to get all entity) is returned.
- `forceInternalID`
/ *Condition*: optional / *Type*: bool / *Default*: False /
If True, force to return the url of resource as internal ID.

Returns:

- `integrationURL`
/ *Type*: str /
The interaction URL of provided resource and ID.

3.2.7 Method: webIDfromResponse

Get internal ID (number) from response of POST method.

Note: Only executionresult has response text. Other resources has only response header.

Arguments:

- response
/ Condition: required / Type: str /
The xml response from POST method for parsing ID information.
- tagID
/ Condition: optional / Type: str / Default: 'rqm:resultId' /
Tag name which contains ID information.

Returns:

- resultId
/ Type: str /
The internal ID (as number).

3.2.8 Method: webIDfromGeneratedID

Return web ID (ns2:webId) from generate ID by get resource data from RQM.

Note:

- This method is only used for generated testcase, executionworkitem and executionresult.
- buildrecord and configuration does not have ns2:webId in response data.

Arguments:

- resourrrceType
/ Condition: required / Type: str /
The RQM resource type.
- generateID
/ Condition: required / Type: str /
The Slug ID which is returned in Content-Location from POST response.

Returns:

- webID
/ Type: str /
The web ID (as number).

3.2.9 Method: getResourceByID

Return data of provided resource and ID by GET method

Arguments:

- resourrrceType
/ Condition: required / Type: str /
The RQM resource type.

- `id`
/ *Condition*: required / *Type*: str /
ID of resource.

Returns:

- `res`
/ *Type*: Response object /
Response data of GET request.

3.2.10 Method: getAllByResource

Return all entries (in all pages) of provided resource by GET method.

Arguments:

- `resourrrceType`
/ *Condition*: required / *Type*: str /
The RQM resource type.

Returns:

- `dReturn`
/ *Type*: dict /
A dictionary which contains response status, message and data.
Example:

```
{
  'success' : False,
  'message' : '',
  'data'    : {}
}
```

3.2.11 Method: getAllBuildRecords

Get all available build records of project on RQM and store them into `dBuildVersion` property.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.12 Method: getAllConfigurations

Get all available configurations of project on RQM and store them into `dConfiguration` property.

Arguments:

(no arguments)

Returns:

(no returns)

3.2.13 Method: getAllTeamAreas

Get all available team-areas of project on RQM and store them into `dTeamAreas` property.

Example:

```
{
  'teamA' : '{host}/qm/process/project-areas/{project-id}/team-areas/{teamA-id}',
  'teamB' : '{host}/qm/process/project-areas/{project-id}/team-areas/{teamB-id}'
}
```

Arguments:*(no arguments)***Returns:***(no returns)***3.2.14 Method: addTeamAreaNode**

Append team-area node which contains URL to given team-area into xml template.

Note: team-area information is case-casesensitive

Arguments:

- root
/ Condition: required / Type: Element object /
The xml root object.
- sTeam
/ Condition: required / Type: str /
Team name to be added.

Returns:

- root
/ Type: str /
The xml root object with addition team-area node.

3.2.15 Method: createTestcaseTemplate

Return testcase template from provided information.

Arguments:

- testCaseName
/ Condition: required / Type: str /
Testcase name.
- sDescription
/ Condition: optional / Type: str / Default: " /
Testcase description.
- sComponent
/ Condition: optional / Type: str / Default: " /
Component which testcase is belong to.
- sFID
/ Condition: optional / Type: str / Default: " /
Function ID (requirement ID) for linking.
- sTeam
/ Condition: optional / Type: str / Default: " /
Team name for linking.

- `sRobotFile`
/ *Condition*: optional / *Type*: str / *Default*: " /
Link to robot file on source control.
- `sTestType`
/ *Condition*: optional / *Type*: str / *Default*: " /
Test type information.
- `sASIL`
/ *Condition*: optional / *Type*: str / *Default*: " /
ASIL information.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.
- `sTCtemplate`
/ *Condition*: optional / *Type*: str / *Default*: None /
Existing testcase template as xml string.
If not provided, template file under RQM_templates is used as default.

Returns:

- `sTCxml`
/ *Type*: str /
The xml testcase template as string.

3.2.16 Method: createTCERTemplate

Return testcase execution record template from provided information.

Arguments:

- `testcaseID`
/ *Condition*: required / *Type*: str /
Testcase ID for linking.
- `testcaseName`
/ *Condition*: required / *Type*: str /
Testcase name.
- `testplanID`
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- `confID`
/ *Condition*: optional / *Type*: str / *Default*: " /
Configuration - Test Environment for linking.
- `sTeam`
/ *Condition*: optional / *Type*: str / *Default*: " /
Team name for linking.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.

Returns:

- sTCERxml
/ *Type*: str /
The xml testcase execution record template as string.

3.2.17 Method: createExecutionResultTemplate

Return testcase execution result template from provided information.

Arguments:

- testcaseID
/ *Condition*: required / *Type*: str /
Testcase ID for linking.
- testcaseName
/ *Condition*: required / *Type*: str /
Testcase name.
- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- TCERID
/ *Condition*: required / *Type*: str /
Testcase execution record (TCER) ID for linking.
- resultState
/ *Condition*: required / *Type*: str /
Testcase result status.
- startTime
/ *Condition*: required / *Type*: str /
Testcase start time.
- endTime
/ *Condition*: optional / *Type*: str / *Default*: " /
Testcase end time.
- duration
/ *Condition*: optional / *Type*: str / *Default*: " /
Testcase duration.
- testPC
/ *Condition*: optional / *Type*: str / *Default*: " /
Test PC which executed testcase.
- testBy
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID who executed testcase.
- lastlog
/ *Condition*: optional / *Type*: str / *Default*: " /
Traceback information (for Failed testcase).

- buildrecordID
/ *Condition*: optional / *Type*: str / *Default*: " /
Build Record ID for linking.
- sTeam
/ *Condition*: optional / *Type*: str / *Default*: " /
Team name for linking.
- sOwnerID
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testcase owner.

Returns:

- sTCResultxml
/ *Type*: str /
The xml testcase result template as string.

3.2.18 Method: createBuildRecordTemplate

Return build record template from provided build name.

Arguments:

- buildName
/ *Condition*: required / *Type*: str /
Build Record name.

Returns:

- sBuildxml
/ *Type*: str /
The xml build template as string.

3.2.19 Method: createConfigurationTemplate

Return configuration - Test Environment template from provided configuration name.

Arguments:

- buildName
/ *Condition*: required / *Type*: str /
Configuration - Test Environment name.

Returns:

- sEnvironmentxml
/ *Type*: str /
The xml test environment template as string.

3.2.20 Method: createTSERTemplate

Return testsuite execution record (TSER) template from provided configuration name.

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID.
- testsuiteName
/ *Condition*: required / *Type*: str /
Testsuite name.
- testplanID
/ *Condition*: required / *Type*: str /
Testplan ID for linking.
- confID
/ *Condition*: optional / *Type*: str / *Default*: " /
Configuration - Test Environment ID for linking.
- sOwnerID
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testsuite owner.

Returns:

- sTSxml
/ *Type*: str /
The xml testsuite template as string.

3.2.21 Method: createTestsuiteResultTemplate

Return testsuite execution result template from provided configuration name.

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID.
- testsuiteName
/ *Condition*: required / *Type*: str /
Testsuite name.
- TSERID
/ *Condition*: required / *Type*: str /
Testsuite execution record (TSER) ID for linking.
- lTCER
/ *Condition*: required / *Type*: str /
List of testcase execution records (TCER) for linking.
- lTCResults
/ *Condition*: required / *Type*: str /
List of testcase results for linking.

- `startTime`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite start time.
- `endTime`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite end time.
- `duration`
/ *Condition*: optional / *Type*: str / *Default*: " /
Testsuite duration.
- `sOwnerID`
/ *Condition*: optional / *Type*: str / *Default*: " /
User ID of testsuite owner.

Returns:

- `sTSResultxml`
/ *Type*: str /
The xml testsuite result template as string.

3.2.22 Method: createResource

Create new resource with provided data from template by POST method.

Arguments:

- `resourceType`
/ *Condition*: required / *Type*: str /
Resource type.
- `content`
/ *Condition*: required / *Type*: str /
The xml template as string.

Returns:

- `returnObj`
/ *Type*: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.23 Method: createBuildRecord

Create new build record.

Arguments:

- sBuildSWVersion
/ Condition: required / Type: str /
Build version - Build Record name.
- forceCreate
/ Condition: optional / Type: bool / Default: False /
If True, force to create new build record without existing verification.

Returns:

- returnObj
/ Type: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.24 Method: createConfiguration

Create new configuration - test environment.

Arguments:

- sConfigurationName
/ Condition: required / Type: str /
Configuration - Test Environment name.
- forceCreate
/ Condition: optional / Type: str / Default: False /
If True, force to create new Test Environment without existing verification.

Returns:

- returnObj
/ Type: dict /
A dictionary reponse which contains status, ID, status_code and error message.
Example:

```
{
  'success' : False,
  'id': None,
  'message': '',
  'status_code': ''
}
```

3.2.25 Method: updateResourceByID

Update data of provided resource and ID by PUT method.

Arguments:

- `resourceType`
/ *Condition*: required / *Type*: str /
Resource type.
- `id`
/ *Condition*: required / *Type*: str /
Resource id.
- `content`
/ *Condition*: required / *Type*: str /
The xml template as string.

Returns:

- `res`
/ *Type*: Response object /
Response object from PUT request.

3.2.26 Method: linkListTestcase2Testplan

Link list of test cases to provided testplan ID.

Arguments:

- `testplanID`
/ *Condition*: required / *Type*: str /
Testplan ID to link given testcase(s).
- `lTestcases`
/ *Condition*: optional / *Type*: list / *Default*: None /
List of testcase(s) to be linked with given testplan.
If not provide, `lTestcaseIDs` property will be used as list of testcase.

Returns:

- `returnObj`
/ *Type*: dict /
Response dictionary which contains status and error message.
Example:

```
{
  'success' : False,
  'message': ''
}
```

3.2.27 Method: linkListTestcase2Testsuite

Link list of test cases to provided testsuite ID

Arguments:

- testsuiteID
/ *Condition*: required / *Type*: str /
Testsuite ID to link given testcase(s).
- lTestcases
/ *Condition*: optional / *Type*: list / *Default*: None /
List of testcase(s) to be linked with given testplan.
If not provide, lTestcaseIDs property will be used as list of testcase.

Returns:

- returnObj
/ *Type*: dict /
Response dictionary which contains status and error message.
Example:

```
{  
  'success' : False,  
  'message': ''  
}
```

Chapter 4

robotlog2rqm.py

4.1 Function: get_from_tags

Extract testcase information from tags.

Example: TCID-xxxx, FID-xxxx, ...

Arguments:

- lTags
/ *Condition:* required / *Type:* list /
List of tag information.
- reInfo
/ *Condition:* required / *Type:* str /
Regex to get the expected info (ID) from tag info.

Returns:

- lInfo
/ *Type:* list /
List of expected information (ID)

4.2 Function: convert_to_datetime

Convert time string to datetime.

Arguments:

- time
/ *Condition:* required / *Type:* str /
String of time.

Returns:

- dt
/ *Type:* datetime object/
Datetime object.

4.3 Function: process_suite_metadata

Try to find metadata information from all suite levels.

Metadata at top suite level has a highest priority.

Arguments:

- suite
/ *Condition*: required / *Type*: TestSuite object /
Robot suite object.
- default_metadata
/ *Condition*: optional / *Type*: dict / *Default*: DEFAULT_METADATA /
Initial Metadata information for updating.

Returns:

- dMetadata
/ *Type*: dict /
Dictionary of Metadata information.

4.4 Function: process_metadata

Extract metadata from suite result bases on DEFAULT_METADATA.

Arguments:

- metadata
/ *Condition*: required / *Type*: dict /
Robot metadata object.
- default_metadata
/ *Condition*: optional / *Type*: dict / *Default*: DEFAULT_METADATA /
Initial Metadata information for updating.

Returns:

- dMetadata
/ *Type*: dict /
Dictionary of Metadata information.

4.5 Function: process_suite

Process robot suite for importing to RQM.

Arguments:

- RQMClient
/ *Condition*: required / *Type*: RQMClient object/
RQMClient object.
- suite
/ *Condition*: required / *Type*: TestSuite object/
Robot suite object.

Returns:

(no returns)

4.6 Function: process_test

Process robot test for importing to RQM.

Arguments:

- RQMClient
/ *Condition*: required / *Type*: RQMClient object/
RQMClient object.
- test
/ *Condition*: required / *Type*: TestCase object/
Robot test object.

Returns:

(no returns)

4.7 Function: RobotLog2RQM

Import robot results from output.xml to RQM - IBM Rational Quality Manager.

Flow to import Robot results to RQM:

1. Process provided arguments from command line
2. Login Rational Quality Management (RQM)
3. Parse Robot results
4. Import results into RQM
5. Link all executed testcases to provided testplan/testsuite ID

Arguments:

- args
/ *Condition*: required / *Type*: ArgumentParser object /
Argument parser object which contains:
 - resultxmlfile : path to the xml result file or directory of result files to be imported.
 - host : RQM host url.
 - project : RQM project name.
 - user : user for RQM login.
 - password : user password for RQM login.
 - testplan : RQM testplan ID.
 - recursive : if True, then the path is searched recursively for log files to be imported.
 - createmissing : if True, then all testcases without tcid are created when importing.
 - updatetestcase : if True, then testcases information on RQM will be updated bases on robot testfile.
 - dryrun : if True, then verify all input arguments (includes RQM authentication) and show what would be done.

Returns:

(no returns)

4.8 Class: Logger

Imported by:

```
from RobotLog2RQM.robotlog2rqm import Logger
```

Logger class for logging message.

4.8.1 Method: config

Configure Logger class.

Arguments:

- `output_console`
/ *Condition*: optional / *Type*: bool / *Default*: True /
Write message to console output.
- `output_logfile`
/ *Condition*: optional / *Type*: str / *Default*: None /
Path to log file output.
- `dryrun`
/ *Condition*: optional / *Type*: bool / *Default*: True /
If set, a prefix as 'dryrun' is added for all messages.

Returns:

(no returns)

4.8.2 Method: log

Write log message to console/file output.

Arguments:

- `msg`
/ *Condition*: optional / *Type*: str / *Default*: " /
Message which is written to output.
- `color`
/ *Condition*: optional / *Type*: str / *Default*: None /
Color style for the message.
- `indent`
/ *Condition*: optional / *Type*: int / *Default*: 0 /
Offset indent.

Returns:

(no returns)

4.8.3 Method: log_warning

Write warning message to console/file output.

Arguments:

- `msg`
/ *Condition*: required / *Type*: str /
Warning message which is written to output.

Returns:

(no returns)

4.8.4 Method: `log_error`

Write error message to console/file output.

- `msg`
/ *Condition*: required / *Type*: str /
Error message which is written to output.
- `fatal_error`
/ *Condition*: optional / *Type*: bool / *Default*: False /
If set, tool will terminate after logging error message.

Returns:

(no returns)

Chapter 5

Appendix

About this package:

Table 5.1: Package setup

| Setup parameter | Value |
|--------------------|--|
| Name | RobotLog2RQM |
| Version | 1.2.1 |
| Date | 14.06.2023 |
| Description | Imports robot result(s) to IBM Rational Quality Manager (RQM) |
| Package URL | robotframework-robotlog2rqm |
| Author | Tran Duy Ngoan |
| Email | Ngoan.TranDuy@vn.bosch.com |
| Language | Programming Language :: Python :: 3 |
| License | License :: OSI Approved :: Apache Software License |
| OS | Operating System :: OS Independent |
| Python required | >=3.0 |
| Development status | Development Status :: 4 - Beta |
| Intended audience | Intended Audience :: Developers |
| Topic | Topic :: Software Development |

Chapter 6

History

| | |
|--|------------|
| 0.1.0 | 07/2022 |
| <i>Initial version</i> | |
| 1.1.1 | 01.08.2022 |
| <i>Rework repository's document bases on GenPackageDoc</i> | |
| 1.1.2 | 25.08.2022 |
| <i>- Correct indent of sourcode's docstring. - Update new style for history.</i> | |
| 1.1.3 | 13.10.2022 |
| <i>- Fix findings and enhance README and document files - Change argument name 'outputfile' to 'resultxmlfile'</i> | |
| 1.1.4 | 10.11.2022 |
| <i>Rename package to RobotLog2RQM</i> | |
| 1.2.0 | 09.01.2023 |
| <i>- Rework optional arguments and improve logging messages - Update README and document for publishing pypi</i> | |
| 1.2.1 | 14.06.2022 |
| <i>Update README: fix links issue and update installation section</i> | |

RobotLog2RQM.pdf*Created at 14.06.2023 - 09:10:48**by GenPackageDoc v. 0.40.3*
